



Category 5E Outdoor Direct Burial AL Foil Shielded F/UTP 24 AWG 4 Pair 8 Solid Bare Copper Conductors, Gel-Filled, Black UV Resistant PE Jacket 1000FT

Applications

- 10/100/1000Base-T
- 100Base-VG
- 155 Mbps and 622-Mbps ATM
- Other high-performance applications
 - Outside Plant
 - Direct Burial
 - Aerial

Compliance

- ISO/IEC 11801
- TIA/EIA-568-C.2 Category 5e
- ANSI/ICEA S-90-661 Category 5e
- NEMA WC63.1 Category 5e
- RoHS Compliance for the Requirement of European Union Issued Directive 2002/95/EC

Physical Characteristics


- Conductor Size: 24AWG
- Conductor Material: Solid Bare Copper
- Insulation Material: High Density Polyethylene (HDPE)
- Insulation Diameter: 1.00 ± 0.03mm
- Number of Conductors: 8 Conductors
- Number of Pairs: 4 Pairs
- Outer Jacket Rip Cord: Yes
- Outer Shield Material: AL Foil
- Drain Wire: Tinned Copper 0.45mm
- Outer Jacket Material: PE (Complies RoHS)
- Outer Jacket Diameter: 6.7mm ± 0.4mm

CAT5E 350MHz Outdoor Solid Direct Burial F/UTP Bulk Cable

CAT5E



Technical Diagram



Available Jacket Colors

- Black Item# C5CMXFS-2279BK

Cable Features

- Tested to 350MHz.
- Meets or Exceeds CAT5E TIA568 C.2 Standards.
- Cable is Marked in Descending Order so You Always Know How Much Cable is Left.
- Extra Headroom Provides Room for Growth.
- Low Attenuation and Power-Sum Crosstalk.

Construction Facts

- This Outdoor Direct Burial Cable has HDPE Insulation.
- AL Foil Shielding is Used to Eliminate Interference in Noisy Environments.
- The Cable is Gel-Filled for Added Moisture Protection.
- Longitudinal Rip Cord for Easy Jacket Opening.

Cable Put-Ups:

- Cable is Supplied in 1000ft Increments on a Wooden Spool.

CAT5E 350MHz Outdoor Direct Burial Shielded Solid Bulk Cable Electrical Specifications

Frequency MHz (Maximum)	ATT dB/100 m (328 ft.) (Maximum)	ACR dB/100 m (328 ft.) (Maximum)	DELAY ns/100 m (328 ft.) (Minimum)	NEXT dB/100 m (328 ft.) (Minimum)	PS-NEXT dB/100 m (328 ft.) (Minimum)	ELFEXT dB/100 m (328 ft.) (Minimum)	PS-ELFEXT dB/100 m (328 ft.) (Minimum)	Return Loss dB (Minimum)
1.0	2.0	N/A	570.00	65.3	62.3	63.8	60.8	20.0
4.0	4.1	N/A	552.00	56.3	53.3	51.8	48.8	23.0
8.0	5.8	N/A	546.73	51.8	48.8	45.7	42.7	24.5
10.0	6.5	N/A	545.38	50.3	47.3	43.8	40.8	25.0
16.0	8.2	N/A	543.00	47.2	44.4	39.7	36.7	25.0
20.0	9.3	N/A	542.05	45.8	42.8	37.8	34.8	25.0
25.0	10.4	N/A	541.20	44.3	41.3	35.8	32.8	24.3
31.25	11.7	N/A	540.44	42.9	39.9	33.9	30.9	23.6
62.5	17.0	N/A	538.55	38.4	35.4	27.9	24.9	21.5
100	22.0	N/A	537.60	35.3	32.3	23.8	20.8	20.1
155	28.1	N/A	536.90	32.4	29.4	20.0	17.0	18.0
200	32.4	N/A	536.50	30.8	27.8	17.8	14.8	17.4
300	41.8	N/A	536.10	29.3	26.3	14.3	11.3	16.5
350	44.9	N/A	535.90	27.1	24.1	12.9	9.9	16.0

PrimusCable.com - (951) 824-1571





CAT5E 350MHz Outdoor Solid Direct Burial F/UTP Bulk Cable

Pair Color Code Chart

- Pair 1 ----- White/Blue Stripe & Blue
- Pair 2 ----- White/Orange Stripe & Orange
- Pair 3 ----- White/Green Stripe & Green
- Pair 4 ----- White/Brown Stripe & Brown

Mechanical Characteristics

- Storage Temperature Range: -30~+60
- Installation Temperature Range: -40~+60
- Operating Temperature Range: -40~+60
- Bulk Cable Weight: N/A / 1000FT
- Max. Recommended Pulling Tension: N/A
- Min. Bend Radius/Minor Axis: N/A
- Min. Bend/Installation: N/A
- Test Object: Jacket
- Test Material: PE
- Before Tensile Strength: ≥ 10.0
 - Aging Elongation: ≥ 125
 - Aging Condition: 100°C x 24hrs x 7Days
- After Tensile Strength: ≥ 8.0
 - Aging Elongation: ≥ 100
 - Cold Bend: No Visible Cracks (-20°C \pm 2°C x 4h)

Electrical Characteristics

- Nom. Mutual Capacitance: N/A
- Nominal Velocity of Propagation: N/A
- Maximum Delay: 537.60 @ 100MHz (ns/100m)
- Maximum Delay Skew: ≤ 45 (ns/100m)
- Maximum Conductor DC Resistance: 9.5 (@ 20°C OHm/100m)
- Maximum Operating Voltage - UL: 300V RMS
- Maximum DCR Unbalanced: 5% (@ 20°C)
- Attenuation (Maximum)
 - 22.0dB/100m (328.1ft.) @ 100MHz
 - 44.9dB/100m (328.1ft.) @ 350MHz
- 1.0 - 100MHz Impedance: 100 Ω \pm 15%
- NEXT (Minimum)
 - 35.3dB/100m (328.1ft.) @ 100MHz
 - 27.1dB/100m (328.1ft.) @ 350MHz
- PS-NEXT (Minimum)
 - 32.3dB/100m (328.1ft.) @ 100MHz
 - 24.1dB/100m (328.1ft.) @ 350MHz
- Return Loss (Minimum)
 - 20.1dB/100m (328.1ft.) @ 100MHz
 - 16.0dB/100m (328.1ft.) @ 350MHz

Jacket Printing

PRIMUS CABLE CAT5E FTP 4PR 24AWG 350MHZ DIRECT BURIAL
(FLOODED) UV OUTDOOR PE TIA/EIA-568-C.2 ZONE A B C D E F /
Device 1 2 3 4 5 6 7 8 9

Sequential foot markers on jacket.

©2016 CRN Solutions Inc. dba. Primus Cable
All Rights Reserved.

Although Primus Cable makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Primus Cable provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Primus Cable be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Primus Cable has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Primus Cable products are subject to Primus Cable's standard terms and conditions of sale.

Primus Cable believes this product to be in compliance with EU RoHS (Directive 2002/EC, 27 Jan 2003). Material manufactured prior to the compliance date may be in stock at Primus Cable facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Primus Cable's knowledge, information, and belief at the date any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification and regulations based on their individual usage of the product.

Primus Cable declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC

PrimusCable.com - (951) 824-1571

