



Threaded Coupler for Copper-Bonded Ground Rod, Sectional – CR34



- High-strength couplings are threaded and chamfered at both ends for easy driving
- Corrosion-resistant couplings ensure permanent, low resistance copper-to-copper connections



| | |
|------------------------------|---------------------------|
| Part Number | CR34 |
| Material | Bronze |
| Ground Rod Diameter, Nominal | 3/4" |
| Length (L) | 76.2 mm |
| Thread Size (TS) | 3/4 UNC |
| Unit Weight | 0.15 kg |
| Certifications | CSA 46866 cULus RUS |
| Standard Packaging Quantity | 25 pc |
| UPC | 78285630674 |

CSA, CSA-US and C-CSA-US are registered trademarks of Canadian Standards Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.