



Metal

Rugged 2Ghz or 5GHz outdoor unit

Completely waterproof, rugged, and super high powered. The serious outdoor wireless device. Fully sealed, industrial design metal case, powered by RouterBOARD and RouterOS.

It has a built-in N-male connector, and pole attachment points, so you can attach it to an antenna directly, or use a standard antenna cable. LED signal indicators make it easy to install and align.

Shipped complete with power injector, adapter and mounting kit. Available in two versions - 2GHz and 5GHz.

CPU	Atheros AR7241 400MHz network processor	
Memory	64MB DDR SDRAM onboard memory	
Ethernet	One 10/100 Mbit/s Fast Ethernet port with Auto-MDI/X, L2MTU up to 2030	
Wireless	Wireless Built-in 5 or 2 GHz 1x1 MIMO, N-male connector,	
Extras	Reset switch, Beeper, Voltage monitor, Temperature monitor	
LEDs	5 wireless signal LEDs, ethernet activity LED (configurable)	
Power options	Passive 8-30V PoE only. 16KV ESD protection on RF port	
Consumption	Up to ~0,5A at 24V (11.5W)	
Dimensions	177x44x44mm, 193g. Must be mounted with ethernet pointing down	
Operating temperature	-30C to +70C	
Operating system	MikroTik RouterOS v5, Level4 license (station, point-to-point or AP modes)	
Package contains	Metal SHPn unit, mounting loops, PoE injector, 24V power adapter	

RX sensitivity	5Hn model	802.11a: -93 dBm @ 6Mbps to -77 dBm @ 54 Mbps 802.11n: -93 dBm @ MCS0 to -71 dBm @ MCS7
	2Hn model	802.11b/g: -93 dBm @ 6Mbps to -77 dBm @ 54 Mbps 802.11n: -92 dBm @ MCS0 to -72 dBm @ MCS7 40MHz
TX power	5Hn model	802.11a: 31dBm @ 6Mbps to 27dBm @ 54 Mbps 802.11n: 30dBm @ MCS0 to 26dBm @ MCS7
	2Hn model	802.11b/g: 32dBm @ 1-11/6Mbps to 29dBm @ 54 Mbps 802.11n: 32dBm @ MCS0 to 28dBm @ MCS7
Modulations		OFDM: BPSK, QPSK, 16 QAM, 64QAM DSSS: DBPSK, DQPSK, CCK