



## PRO-SECTOR24015dual H&V\_BOX

### Key Features:

- 2x15 dBi Sectoral Gain
- Dual Polarization H&V in One Case
- Integrated enclosure
- Special Outdoor Weatherproof Enclosure Dedicated for Mikrotik RouterBOARDS
- High Quality Construction
- Heavy-Duty Mounting Elements
- Easy Elevation and Tilt Adjustment
- 5 Years Warranty
- Designed for All Weather Operation



### Applications:

- 2,4 GHz Band Wireless LAN
- N stream dual configuration
- 802.11b/g MIMO standard
- Point to Multipoint Applications

### Description:

Antenna with multipurpose enclosure working in 2,4 GHz band with two independent sector antennas with 15 dBi gain with vertical and horizontal polarization. It is the ideal solution for MIMO and Nstream dual configuration. The range includes weatherproof outdoor enclosure with panel antenna and enough compartment for RouterBoard or any other electronic equipment. Enclosure is furnished with special RJ-45 waterproof ethernet connector with an easy connection to Internet Network and PoE. Perfectly designed for operation under severe weather conditions. Proper materials allow operation in the salty water environment without corrosion. Professional mounting system with 0-15 degrees scale guarantees easy and smooth tilt down as well as rock-stable operation. This product is well suited to point to multipoint applications for highly professional solutions. Inside the enclosure are suitable posts for **Mikrotik RouterBOARDS 411 and 433 series**.

Electrical Properties	
Frequency	2.4 - 2.5 GHz
Gain	2x15dBi
Polarization	dual H&V
Beamwidth deg horizontal	90°(-3dB), 120°(-6dB)
Beamwidth deg vertical	12°
VSWR	<2
Impedance	50 ohm
Front to back ratio	> 35 dB
Port Isolation	> 45 dB
Lightning protection:	DC ground
Enclosure Properties	
Technology:	Microstrip
Material:	UV protected
Colour:	Grey
Min temperature:	-40°C / -40°F
Max temperature:	80°C / 176°F
Mechanical Properties	
Compatible with:	RB411 and RB433 series
Input Connector	2xUFL pigtail (or MMCX optional)
Enclosure Connector	Waterproof Ethernet Connector RJ45 (or cable gland optional)
Outside Dimensions	580x150x60mm / 22.8x5.9x2.4"
Weight	2.1kg / 4.7lbs

Specification subject to change without notice.