






☎ 1-855-276-(KPPA) 5772 or 780-702-7577
 💻 info@kppperformance.ca
 ✉ 15497 117 Ave, Edmonton, AB T5M3X4, Canada
 ✉ 3000 West Commerce, Dallas, TX 75212, USA

Part Number		KPPA-3GHZ-DPOMA-WC	
Electrical		Mechanical	
Frequency range	3300-3800 MHz	Dimensions	42.5" tall, 3.3" diameter
Polarization	Vertical and Horizontal	Weight	7.9 lb
Gain	13 dBi	Mounting method	Mast
Elevation 3dB beamwidth	7 °	Mounting pole dia	1.6 – 2.4"
Electrical Downtilt	1 °	Radome material	UV resistant PVC
VSWR	< 2:1	Environmental	
Return loss	> 10 dB	Temperature range	-40° to +65° C / +150° F
Cross-pol ratio	> 20 dB	Wind speed	210 km/h / 130 mph
V-H port isolation	> 30 dB	UV protection	UV resistant PVC
Input power	50 W max per port	Ingress protection	IP54 rain resistant
Impedance	50 Ω	Lightning protection	DC Ground
Connector Type	Type N Female x 2		



Azimuth patterns

Elevation patterns



VSWR

Gain

