

AV1000 Gigabit Powerline Starter Kit

Smooth HD Streaming in Every Room










Highlights

HomePlug AV2 Standard Compliant


The HomePlug AV2 standard creates high-speed data transfer rates of up to 1000Mbps to support all your online activities.

Gigabit Ethernet for Fast Connections

One Gigabit Ethernet port provides reliable high-speed wired connections for game consoles, smart TVs, STB and more.








TL-PA7010 KIT

Highlights

Plug and Play!

Internet from Any Outlet



Powerline adapters and extenders must be deployed in a set of two or more.

TL-PA7010 KIT

Features



 Ultra-fast Powerline Speed – HomePlug AV2 standard compliant, high-speed data transfer rate of up to 1000Mbps, ideal for Ultra HD streaming and online gaming



• 300-meter Range – Up to 300-meter range over the household power circuit.



- Plug and play Plug and play, no configuration required
- No new wires No new wires, use existing electrical wiring to expand your home network
- TP-Link tpPLC Allows you to easily manage your network using the intuitive tpPLC App or the tpPLC Utility



 Pair Button – 128-bit AES encryption easily at a push of "Pair" Button



• Power Saving – Power Saving Mode helps reducing power consumption by up to 85%


Specifications

Hardware

- · Plug Type: EU
- Standards and Protocols: HomePlug AV2, HomePlug AV, IEEE 1901, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
- Power Consumption: Maximum: 2.72W Typical: 2.3W

Standby: 0.5W

- · Range: 300 Meters over electrical circuit
- Interface: 1 * Gigabit Ethernet Port
- Button: Pair Button
- LED Indicator: Power, Powerline, Ethernet
- Dimensions (W x D x H): $3.8 \times 2.4 \times 1.4$ in. ($98 \times 60 \times 36$ mm)



- Modulation Technology: OFDM (PLC)
- Encryption: Powerline Security: 128-bit AES

Others

- · Certification: CE, RoHS
- · Package Contents:
- Powerline Ethernet Adapter 2×Ethernet Cable Quick Installation Guide
- System Requirements:
- Environment:

Operating Temperature: 0°C~40°C (32°F ~104°F) Storage Temperature: -40°C~70°C (-40°F ~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing



For more information, please visit

http://www.tp-link.com/en/products/details/cat-18 TL-PA7010-KIT.html

or scan the QR code left

Specifications are subject to change without notice. TP-Link is a registered trademarks or registered trademarks of their respective holders. Copyright @ 2016 TP-Link Technologies Co., Ltd. All rights reserved. * Compatible with all HomePlug AV & AV2 Standard Powerline adapters.

* Listed AV and Wi-Fi speeds refer to the theoretical maximum physical-layer data transfer rate. Actual data speeds vary and are influenced by the home's Wi-Fi/electrical/physical environment, and if adapters are placed on the same home circuit.

* Utility supports Windows 10/8.1/8/7/Vista/XP and Mac OS X (10.7 or later) operating system for the present.

Windows 2000/XP/2003/Vista/7/8/8.1/10, Mac, Linux

www.tp-link.com

TP-Link AV1000 Gigabit Powerline Starter Kit

TL-PA7010 KIT