

TwistPort™ Adaptor for ePMP-B

INTEGRATES EPMP CONNECTORIZED RADIOS INTO TWISTPORT™ ECO-SYSTEM

The TwistPort™ Adaptor TP-ADAP-e2K makes the ePMP™ 2000AP, ePMP™ Force 400C, ePMP™ Force 4600C, ePMP™ Force 4600L and ePMP™ 4500L radio compatible with all TwistPort™ Antennas. TwistPort™ Adaptors are equipped with our original quick-locking waveguide port. Connecting and disconnecting the radios with the TwistPort™ Adaptor is very simple and requires no tools.



TECHNICAL DATA

| | |
|--------------------|--|
| Antenna Connection | TwistPort™ - Quick-Locking Waveguide Port |
| Radio Connection | 2x Slide-On RP-SMA |
| Materials | Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic |
| Flame Rating | UL 94 HB |
| Temperature | -40°C to +60°C (-40°F to +140°F) |
| Wind Survival | 160 km/h (100 miles/h) |
| Weight | 0.42 Kg (0.9 lbs) – single unit 0.52 Kg (1.1 lbs) – single unit incl. package 11.5 Kg (25.3 lbs) – carton (20 units) |
| Single Unit | Retail Box: 109 x 98 x 54 mm (4.3 x 3.8 x 2.1 inch) |
| 20 Units | Carton Box: 361 x 609 x 325 mm (14.2 x 23.9 x 12.8 inch) |

PERFORMANCE

| | |
|-----------------|---|
| Frequency Range | See antenna datasheet for frequency range |
| Polarization | Dual Linear H + V |
| VSWR Max | 1.8 |
| Impedance | 50 Ohm |

COMPATIBLE WIRELESS PLATFORMS

| | |
|-------------------|--|
| RF elements® | any TwistPort™ Antenna |
| Cambium Networks™ | ePMP 2000 AP, ePMP Force 400C, Force 4600C, Force 4600L and ePMP 4500L |

PACKAGE CONTENTS

TwistPort™ Adaptor

PRODUCT DIMENSIONS

