

Product data sheet

Characteristics

PRM24

APC 24 position chassis for replaceable data line surge protection modules, 19" rackmount, 1U



Overview

Model Name	<![CDATA[APC 24 position chassis for replaceable data line surge protection modules, 19" rackmount, 1U]]>
Includes	User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Afghanistan , Albania , Algeria , Andorra , Angola , Anguilla , Antigua And Barbuda , Argentina , Armenia , Aruba , Australia , Austria , Azerbaijan , Bahrain , Bangladesh , Barbados , Belarus , Belgium , Belize , Benin , Bhutan , Bolivia , Bosnia And Herzegovina , Botswana , Brazil , Brunei Darussalam , Bulgaria , Burkina Faso , Burundi , Cambodia , Cameroon , Canada , Cayman Islands , Central African Republic , Chad , Chile , Colombia , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Cook Islands , Costa Rica , <![CDATA[Cote D'Ivoire]]> , Croatia , Cuba , Cyprus , Czech Republic , Denmark , Djibouti , Dominican Republic , East Timor , Ecuador , Egypt , El Salvador , Equatorial Guinea , Eritrea , Estonia , Ethiopia , Falkland Islands (Malvinas) , Fiji , Finland , France , Gabon , Gambia , Georgia , Germany , Ghana , Gibraltar , Greece , Guatemala , Guinea , Guyana , Honduras , Hong Kong , Hungary , Iceland , India , Indonesia , Iraq , Ireland , Israel , Italy , Jamaica , Jordan , Kazakhstan , Kenya , KOREA, REPUBLIC OF , Kuwait , Latvia , Lebanon , Lesotho , Liberia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Malawi , Malaysia , Mali , Malta , Mauritania , Mexico , Moldova , Republic Of , Mongolia , Morocco , Mozambique , Myanmar , Namibia , Nepal , Netherlands , Netherlands Antilles , New Zealand , Nicaragua , Niger , Nigeria , Norway , Oman , Pakistan , Panama , Papua New Guinea , Paraguay , Peru , Philippines , Poland , Portugal , Puerto Rico , Romania , Russian Federation , Rwanda , Saudi Arabia , Senegal , Sierra Leone , Singapore , Slovakia (Slovak Republic) , Slovenia , Somalia , South Africa , Spain , Sri Lanka , Sudan , Suriname , Sweden , Switzerland , Taiwan , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Thailand , Togo , Trinidad And Tobago , Tunisia , Turkmenistan , Uganda , Ukraine , United Arab Emirates , United States , Uruguay , Uzbekistan , Venezuela , Viet Nam , VIRGIN ISLANDS (UNITED STATES) , Western Sahara , Yemen , Zambia , Zimbabwe

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Output

Number of Outlets	24
-------------------	----

Input

Input Power	0 W
Maximum Line Current per phase	0.0 A
Maximum Input Current	0 A

Surge Protection and Filtering

EMI/RFI Noise rejection (100 kHz to 10 MHz)	0.0 dB
---------------------------------------------	--------

Peak Current Common Mode	0.0 kA
NM Surge Response Time (ns)	0.0 ns

Physical

Net Weight	1.24 kg
Maximum Height	44.0 mm
Maximum Width	479.0 mm
Maximum Depth	89.0 mm
Shipping Weight	1.74 kg
Shipping Height	142.0 mm
Shipping Width	574.0 mm
Shipping Depth	142.0 mm
Master Carton Units	6.0
Master Carton Weight	28.0 lbs
SCC Codes	2073130420268 8
Color	Black
Units per Pallet	12.0

Environmental

Operating Environment	-15 - 45 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-3000 meters

Conformance

Approvals	CE , UL 1950 , VDE
Standard warranty	Lifetime

Sustainable Offer Status

RoHS	Compliant
Other Environmental Compliance	China RoHS