



Category 5E UTP 500' 8 Conductor, Bulk, PVC Jacket, 24AWG Solid-Bare Copper, Pull Box (ETL)

Applications

- 10/100/1000Base-T
- 100Base-VG
- 155 Mbps and 622-Mbps ATM
- Other high-performance applications
 - Backbone
 - Floor-to-floor backbone
 - Horizontal cabling to desktop

Compliance

- ISO/IEC 11801
- TIA/EIA-568-C.2 Category 5e
- ANSI/ICEA S-90-661 (Category 5)
- NEMA WC63.1 (Category 5)
- PVC: CM
- ETL Verified
- RoHS Compliance for the Requirement of European Union Issued Directive 2002/95/EC

Physical Characteristics


- Conductor Size: 24AWG
- Conductor Material: Solid Bare Copper
- Insulation Material: High Density Polyethylene
- Insulation Diameter: $0.86 \pm 0.03\text{mm}$
- Number of Conductors: 8 Conductors
- Number of Pairs: 4 Pairs
- Outer Shield Material: N/A
- Drain Wire: No
- Outer Jacket Material: PVC CM (RoHS Compliant)
- Outer Jacket Diameter: $4.9\text{mm} \pm 0.4\text{mm}$
- Outer Jacket Rip Cord: Yes

CAT5E 350MHz Solid Unshielded Bulk Cable

CAT5E



Technical Diagram



Available Jacket Colors

- Blue Item# C5U-2432BL-5
- White Item# C5U-2433WH-5

Cable Features

- Tested up to 350MHz.
- Meets or exceeds CAT5e TIA/EIA-568-C.2 standards.
- Easy to use pull box with bigger payout.
- Cable is marked in descending order so you always know how much cable is in the box.
- Extra headroom provides room for growth.
- Low attenuation and power-sum crosstalk.

Construction Facts

- The PVC Cable has high density polyethylene insulation.
- Longitudinal rip cord for easy jacket opening.

Cable Put-Ups:

- Cable is supplied in 500ft increments in a pull box.

CAT5E 350MHz Solid Bulk Cable Electrical Specifications

Frequency MHz (Maximum)	ATT dB/100 m (328 ft.) (Maximum)	ACR dB/100 m (328 ft.) (Maximum)	Delay ns/100 m (328 ft.) (Minimum)	NEXT dB/100 m (328 ft.) (Minimum)	PS-NEXT dB/100 m (328 ft.) (Minimum)	ELFEXT dB/100 m (328 ft.) (Minimum)	PS-ELFEXT dB/100 m (328 ft.) (Minimum)	Return Loss dB (Minimum)
1	2.0	N/A	570.0	65.3	62.3	63.8	60.8	20.0
4	4.1	N/A	552.00	56.3	53.3	51.8	48.8	23.0
8	5.8	N/A	546.73	51.8	48.8	45.7	42.7	24.5
10	6.5	N/A	545.38	50.3	47.3	43.8	40.8	25.0
16	8.2	N/A	543.00	47.2	44.4	39.7	36.7	25.0
20	9.3	N/A	542.05	45.8	42.8	37.8	34.8	25.0
25	10.4	N/A	541.20	44.3	41.3	35.8	32.8	24.3
31.25	11.7	N/A	540.44	42.9	39.9	33.9	30.9	23.6
62.50	17.0	N/A	538.55	38.4	35.4	27.9	24.9	21.5
100	22.0	N/A	537.60	35.3	32.3	23.8	20.8	20.1
155	28.1	N/A	536.90	32.4	29.4	20.0	17.0	18.0
200	32.4	N/A	536.50	30.8	27.8	17.8	14.8	17.4
300	41.8	N/A	536.10	29.3	26.3	14.3	11.3	16.5
350	44.9	N/A	535.90	27.1	24.1	12.9	9.9	16.0

PrimusCable.com - (951) 824-1571





CAT5E 350MHz Solid Unshielded Bulk Cable

Pair Color Code Chart

- Pair 1 ----- White/Blue Stripe & Blue
- Pair 2 ----- White/Orange Stripe & Orange
- Pair 3 ----- White/Green Stripe & Green
- Pair 4 ----- White/Brown Stripe & Brown

Mechanical Characteristics

- Storage Temperature Range: -30~+60
- Installation Temperature Range: -30~+60
- Operating Temperature Range: -30~+60
- Bulk Cable Length: 500FT
- Max. Recommended Pulling Tension: 25lbs.
- Min. Bend Radius/Minor Axis: 0.800 in.
- Min. Bend/Installation: 1.900 in.
- Test Object: Jacket
- Test Material: PVC
- Before Tensile Strength: ≥ 13.5
 - Aging Elongation: ≥ 150
 - Aging Condition: 100°C x 24hrs x 7Days
- After Tensile Strength: ≥ 12.5
 - Aging Elongation: ≥ 125
 - Cold Bend: No Cracks (-40°C \pm 2°C x 4hrs)

Electrical Characteristics

- Nom. Mutual Capacitance: 15 (p /ft)
- Nominal Velocity of Propagation: 69 (VP %)
- Maximum Delay: 538 @ 100MHz (ns/100m)
- Maximum Delay Skew: ≤ 45 (ns/100m)
- Maximum Conductor DC Resistance: 11.5 (@ 20°C OHm/100m)
- Maximum Operating Voltage - UL: 300V RMS
- Maximum DCR Unbalanced: 5% (@ 20°C)
- Attenuation (Maximum)
 - 22.0dB/100m (328.1ft.) @ 100MHz
 - 44.9dB/100m (328.1ft.) @ 350MHz
- 1.0 - 100MHz Impedance: $100\Omega \pm 15\%$
- NEXT (Minimum)
 - 35.3dB/100m (328.1ft.) @ 100MHz
 - 27.1dB/100m (328.1ft.) @ 350MHz
- PS-NEXT (Minimum)
 - 32.3dB/100m (328.1ft.) @ 100MHz
 - 24.1dB/100m (328.1ft.) @ 350MHz
- Return Loss (Minimum)
 - 20.1dB/100m (328.1ft.) @ 100MHz
 - 16.0dB/100m (328.1ft.) @ 350MHz

Jacket Printing

PRIMUS CABLE CAT5E UTP 4PR 24AWG 350MHZ CM ETL
VERIFIED TO ANSI/TIA-568-B.2 ZONE A B C D E F /
DEVICE 1 2 3 4 5 6 7 8 9 (VID:018) XXXFT

Sequential foot markers on jacket.

©2016 CRN Solutions Inc. dba. Primus Cable
All Rights Reserved.

Although Primus Cable makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Primus Cable provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Primus Cable be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Primus Cable has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Primus Cable products are subject to Primus Cable's standard terms and conditions of sale.

Primus Cable believes this product to be in compliance with EU RoHS (Directive 2002/EC, 27 Jan. 2003). Material manufactured prior to the compliance date may be in stock at Primus Cable facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Primus Cable's knowledge, information, and belief at the date any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification and regulations based on their individual usage of the product.

Primus Cable declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC

PrimusCable.com - (951) 824-1571

