



Category 5E UTP 1000' 50 Conductors, Bulk, PVC Jacket, 24AWG Solid-Bare Copper, Wooden Spool (ETL). Our bulk cable is marked in descending order so you always know how much cable is left.

**Applications**

- Gigabit Ethernet 1000Base-T
- 100Base-T and 100Base-TX
- 100Base-VG AnyLAN
- 55/155 Mbps ATM
- High Speed Voice/Data Applications
- ISDN and Multimedia

**Compliance**

- ISO/IEC 11801
- TIA/EIA-568-C.2 Category 5e
- ANSI/ICEA S-90-661 (Category 5)
- NEMA WC63.1 (Category 5)
- PVC: CM
- ETL Verified
- RoHS Compliant

**Physical Characteristics**


- Conductor Size: 24AWG
- Conductor Material: Solid Bare Copper
- Insulation Material: Polyethylene
- Insulation Diameter: 0.90 ± 0.02mm
- Number of Conductors: 50 Conductors
- Number of Pairs: 25 Pairs
- Outer Shield Material: N/A
- Drain Wire: No
- Outer Jacket Material: CM PVC
- Outer Jacket Diameter: .520 in.
- Outer Jacket Rip Cord: Yes - Nylon

# CAT 5E 350Mhz Solid 25 Pair Unshielded Bulk Cable

**CAT5E**



**Technical Diagram**



**Available Jacket Colors**

- Gray Item# C5U-368GY-50C

**Cable Features**

- Uniformity of Insulation Provides Very Low Differential Propagation Delay (Skew).
- Meets or Exceeds CAT 5E T568C Standards.
- Easy to Use Wooden Spool.
- Extra Headroom Provides Room for Growth.
- Low Attenuation and Power-Sum Crosstalk.

**Construction Facts**

- The PVC Cable has Polyethylene Insulation.
- Longitudinal Rip Cord for Easy Jacket Opening.

**Cable Put-Ups:**

- Cable is Supplied in 1000ft Increments on a Wooden Spool.

### CAT 5E 350MHz Solid Bulk Cable Electrical Specifications

Frequency MHz (Maximum)	ATT dB/100 m (328 ft.) (Maximum)	ACR dB/100 m (328 ft.) (Maximum)	DELAY ns/100 m (328 ft.) (Minimum)	NEXT dB/100 m (328 ft.) (Minimum)	PS-NEXT dB/100 m (328 ft.) (Minimum)	ELFEXT dB/100 m (328 ft.) (Minimum)	PS-ELFEXT dB/100 m (328 ft.) (Minimum)	Return Loss dB (Minimum)
1.0	2.0	N/A	570.00	62.3	62.3	61.0	61.0	17.0
4.0	4.1	N/A	552.00	53.3	53.3	49.0	49.0	18.8
8.0	5.8	N/A	546.73	48.8	48.8	42.9	42.9	19.7
10.0	6.5	N/A	545.38	47.3	47.3	41.0	41.0	20.0
16.0	8.2	N/A	543.00	44.2	44.4	36.9	36.9	20.0
20.0	9.3	N/A	542.05	42.8	42.8	35.0	35.0	20.0
25.0	10.4	N/A	541.20	41.3	41.3	33.8	33.0	19.3
32.25	11.7	N/A	540.44	39.9	39.9	31.1	31.1	18.6
62.5	17.0	N/A	538.55	35.4	35.4	25.1	25.1	16.5
100	22.0	N/A	537.60	32.3	32.3	21.0	21.0	15.1
200	32.0	N/A	536.50	27.8	27.8	14.8	14.8	13.0
350	44.9	N/A	535.90	24.1	24.1	9.9	9.9	11.3

PrimusCable.com - (951) 824-1571





## CAT 5E 350Mhz Solid 25 Pair Unshielded Bulk Cable

### Pair Color Code Chart

Pair 1 ---- White - Blue	Pair 14 ---- Black - Brown
Pair 2 ---- White - Orange	Pair 15 ---- Black - Gray
Pair 3 ---- White - Green	Pair 16 ---- Yellow - Blue
Pair 4 ---- White - Brown	Pair 17 ---- Yellow - Orange
Pair 5 ---- White - Gray	Pair 18 ---- Yellow - Green
Pair 6 ---- Red - Blue	Pair 19 ---- Yellow - Brown
Pair 7 ---- Red - Orange	Pair 20 ---- Yellow - Gray
Pair 8 ---- Red - Green	Pair 21 ---- Violet - Blue
Pair 9 ---- Red - Brown	Pair 22 ---- Violet - Orange
Pair 10 ---- Red - Gray	Pair 23 ---- Violet - Green
Pair 11 ---- Black - Blue	Pair 24 ---- Violet - Brown
Pair 12 ---- Black - Orange	Pair 25 ---- Violet - Gray
Pair 13 ---- Black - Green	

### Mechanical Characteristics

- Storage Temperature Range: -30~+60
- Installation Temperature Range: -30~+60
- Operating Temperature Range: -30~+60
- Bulk Cable Weight: 120lbs. / 1000FT
- Max. Recommended Pulling Tension: 119 lbs.
- Min. Bend Radius: 4.900 in.
- Test Object: Jacket
- Test Material: PVC
- Before Tensile Strength:  $\geq 13.8$ 
  - Aging Elongation:  $\geq 100$
  - Aging Condition: 100°C x 168hrs
- After Tensile Strength:  $\geq 85\%$  Mpa
  - Aging Elongation:  $\geq 50\%$
  - Cold Bend: No Cracks (-40°±2° Cx4hrs)

### Electrical Characteristics

- Capacitance Unbalance Pair to Ground, max: 330 pF/100m
- Maximum Conductor DC Resistance: 9.38  $\Omega$ /100m
- Dielectric Strength: 1,000 V RMS @ 60Hz for 1 Minute
- Voltage Rating: 150 VAC maximum
- Current Rating: 1.5 A maximum
- Insulation Resistance: 500 Mega  $\Omega$  minimum
- Contact Resistance: 10 Milli  $\Omega$  maximum
- Maximum Delay: 538 @ 100MHz (ns/100m)
- Maximum Delay Skew:  $\leq 45$  (ns/100m)
- Maximum DCR Unbalanced: 5% (@ 20°C)
- Attenuation (Maximum)
  - 22.0dB/100m (328.1ft.) @ 100MHz
  - 44.9dB/100m (328.1ft.) @ 350MHz
- 1.0 - 100MHz Impedance: 100 $\Omega$   $\pm$  15%
- NEXT (Minimum)
  - 35.3dB/100m (328.1ft.) @ 100MHz
  - 27.1dB/100m (328.1ft.) @ 350MHz
- PS-NEXT (Minimum)
  - 32.3dB/100m (328.1ft.) @ 100MHz
  - 24.1dB/100m (328.1ft.) @ 350MHz
- Return Loss (Minimum)
  - 20.1dB/100m (328.1ft.) @ 100MHz
  - 16.0dB/100m (328.1ft.) @ 350MHz

### Jacket Printing

PRIMUS CABLE CAT5E UTP 25PR 24AWG 350MHZ CM ETL  
VERIFIED TO TIA/EIA-568B.2 ZONE A B C D E F /  
DEVICE 1 2 3 4 5 6 7 8 9(VID:018)XXXXFT

Sequential foot markers on jacket.

©2013 CRN Solutions Inc. dba. Primus Cable  
All Rights Reserved.

Although Primus Cable makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Primus Cable provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Primus Cable be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Primus Cable has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Primus Cable products are subject to Primus Cable's standard terms and conditions of sale.

Primus Cable believes this product to be in compliance with EU RoHS (Directive 2002/EC, 27 Jan. 2003). Material manufactured prior to the compliance date may be in stock at Primus Cable facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Primus Cable's knowledge, information, and belief at the date any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification and regulations based on their individual usage of the product.

Primus Cable declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC

PrimusCable.com - (951) 824-1571

