

# Product Data Sheet

☎ 1-855-276-(KPPA) 5772 or 780-702-7577  
📧 info@kpperformance.ca  
✉ 15497 117 Ave, Edmonton, AB T5M3X4, Canada  
✉ 5000 W. Proviso Dr, Unit #2 Melrose Park, IL 60163, USA



## RK24EWIFIDBI-4LD

Cambium Radio Reflector Dish 28" Metal Mount

- Compatible with Cambium PMP100, 430, and 450 Radios
- Improves performance and range in LOS and NLOS
- Easy installation and robust design, ROHS compliant

### Electrical Specification

Frequency Band	GHz	2	3	5
Reflector Gain	dBi	21±0.5	23±0.5	27±0.5
Polarization		Slant or H/V	Slant or H/V	Slant or H/V
Horizontal HPBW	Degree	10	7	5
Vertical HPBW	Degree	13	10	7
Front to Back Ratio	dB	23	25	25

### Mechanical Specifications

Electrical Grounding	Reflector grounded to mounting bracket
Surface Finish	UV resistant matt powder coat
Wind Load, frontal	414N @ 140km/h   93 lbf @ 87mph
Max. Wind Speed	160km/h   100mph
Mounting Type	J-Arm mount in kit

### Reflector Dimensions

Length	648 mm   25.5 in
Width	584 mm   23 in
Height	711 mm   28 in
Net Weight, with brackets	5.9 kg   13 lb

ANTENNAS ENGINEERED & MANUFACTURED TO EXCEED INDUSTRY STANDARDS