



\* NOTE: OLDER CD ROTORS USED 4 - 5/8" DIA. BOLTS FOR WHICH THIS DRAWING SHOWED 4 - 5/8" DIA. HOLES. THE LATEST CD ROTORS USE 6 - 5/8" DIA. BOLTS. IT IS FEEL, HOWEVER, THAT ONLY FOUR BOLTS WILL BE SUFFICIENT.

STAMP PIN	PIN	4
AS25G	KH1254	

**BILL OF MATERIAL ASSY. PIN AS25G**

ITEM	QUAN.	PART NO.	DESCRIPTION	DRG. NO.
1		KH1254	ACCESSORY SHELF, NO. 25	C750097R6
3		UR454	U-BOLT ASSY 1/4 X 1-1/4 ZPP	8651020R20

NO.	DESCRIPTION	DATE	BY
R0	ADDED BILL OF MATERIAL	4-23-80	UMD
R1	REMOVED AS25G PART	4-15-80	UES
R2	CHANGED 12 GAGE TO 12 GAGE	3-17-80	UES
R3	ADDED AS25G PIN & BEND NOTE	4-26-80	UES
R4	2 1/8" WAS 2 1/8"	4-10-80	UMD
R5	CHANGED & ADDED ROTOR HOLES	7-16-80	ARD
R6	REMOVED HOLES 2 1/2" LEFT FRONT OF CENTER	6-9-80	ARD
R7	ADDED STAMP NOTE	4-16-77	UMC
R8	REVISED CENTER HOLES	3/18/77	UES
R9	REVISED MAT GAGE	5-2-76	UES

**ROHN MANUFACTURING**

TITLE  
ACCESSORY SHELF FOR NO. 25G TOWERS  
ASSY. PT. NO. AS25G

SCALE	NONE	DATE	2-7-75
DRW. BY	RDB	DATE	2-19-75
CHKD. BY	UMD	DATE	2-20-75
APP'D. BY	UMD	DATE	6-13-78
DESIGNED BY	UMD	DATE	
DWG. NO.	C750097	REV.	R6