

NEW
PROLINE
PARABOLIC
ANTENNAS



Same-Day Shipping ✓

Largest In-Stock Selection ✓

Expert Technical Support ✓

an INFINIT[®] company

NEW

ProLine Parabolic Antennas



Our new high-performance **ProLine Parabolic Antennas** are engineered to suppress side-lobes and back-lobes and are excellent at rejecting interference. Available in 1-foot & 2-foot diameters with gain performance of 24 dBi and 29 dBi respectively, these antennas are perfectly suited for high density point-to-point client-premises or backhaul applications.

These antennas maximize the potential of your radio by improving signal strength and reducing the noise floor in your link. The innovative design and assembly feature **patent pending** quick-connect waveguide technology that allows rapid installation in minutes. Customers can choose from a connectorized waveguide launcher with N-type female connectors or a weatherproofed, cable-less, push-in adapter designed specifically for the Mimosa® C5c™ radio.

Features

- 2-foot & 1-foot dish diameter options available
- Gain performance of 24 dBi (1-foot dish) & 29 dBi (2-foot dish)
- Stable gain over ultra-wide bandwidth of 4.9 GHz - 6.4 GHz
- Optimized F/B & side-lobe suppression minimizes interference
- 2 x N-type connectors or push-in adapter for the Mimosa® C5c™
- Built-in universal pipe-mount bracket for connectorized radio
- Mimosa® C5c™ push-in adapter is fully weatherproofed
- Patent Pending Quick-Connect Waveguide technology
- Installs in minutes to reduce service calls and installation time
- Quick connect waveguide allows rapid change of polarization
- Heavy-duty bracket with fine elevation and azimuth adjustment
- Mounts to any size mast from 0.75" to 4.5"

Specifications



SKU	Price	SKU	Price
KP-5PDC5C-1	\$119.99	KP-5PDC5C-2	\$179.99
KP-5PDN-1	\$119.99	KP-5PDN-2	\$179.99
	2-Foot Radome	KP-5PDR-2	\$49.95
Diameter	15" (1-Foot)		25" (2-Foot)
Frequency Band	4900-6400 MHz		
Gain	24 dBi	29 dBi	
Polarization	H/V or ±45 Slant		
Horizontal HPBW	9°	5°	
Vertical HPBW	9°	5°	
Front-to-Back Ratio @ 180°±30°	35 dB	40 dB	
Cross-polarization Ratio over HPBW	25 dB	32 dB	
VSWR	1.5	1.5	
Return Loss	14 dB	14 dB	
Port-to-Port Isolation	30 dB	30 dB	
Impedance	50 Ohms		
Antenna Input	Mimosa C5c Adapter or 2 x N-Type Female Connectors		
Color	Grey		
Wind Velocity, Operational	145 km/h (90 mph)		
Mounting Pole Diameter	19 mm – 114 mm (0.75 in – 4.5 in)		

1-Foot Dish





KP-5PDC5C-1

KP-5PDN-1



Azimuth Patterns 15"





Elevation Patterns 15"

2-Foot Dish





KP-5PDC5C-2

KP-5PDN-2



Azimuth Patterns 25"



Elevation Patterns 25"