

HP4-2.4

1.2 M | 4 FT HIGH PERFORMANCE PARABOLIC REFLECTOR ANTENNA, SINGLE-POLARIZED, 2.4-2.7GHZ

The HP High Performance Series by RadioWaves offers a full line of high performance parabolic antennas engineered to provide ETSI class 2/3 radiation pattern performance as well as excellent gain. RadioWaves field-proven pre-assembled antennas and robust pole-mounts ensure “set and forget” installation with minimal post-installation maintenance. The included radome ensures robust and reliable performance under the most challenging conditions. If it's rugged, it must be RadioWaves!



FEATURES AND BENEFITS

- High Performance ETSI Class 2/3* Parabolic Antennas – Excellent performance for a wide range of applications
- Fully Preassembled at the Factory – Simplifies installation on site and guarantees “factory-tested” quality
- Warranty – Industry leading 7-year warranty

*ETSI Class depends on frequency band

SPECIFICATIONS

General

| | | | |
|---------------|--|------------------------------|------------------------------------|
| Antenna Type | High Performance Parabolic Reflector Antenna | Standard RF Connector Type | N-Female |
| Size, nominal | 4 ft 1.2 m | Standard RF Connector Suffix | NS (append suffix to model number) |
| Polarization | Single | | |

Electrical

| | | | |
|-----------------------------------|---------------|----------------------|----------|
| Operating Frequency Band | 2.4 - 2.7 GHz | Gain, Low Frequency | 26.5 dBi |
| Half Power Beamwidth, Horizontal | 7.3 degrees | Gain, Mid Frequency | 27 dBi |
| Half Power Beamwidth, Vertical | 7.3 degrees | Gain, High Frequency | 27.5 dBi |
| Cross-Polarization Discrimination | 30 dB | VSWR | 1.5:1 |
| Front to Back Ratio (F/B) | 42 dB | Return Loss | -14 dB |

Mechanical

| | |
|-------------------------------|--------------------|
| Fine Azimuth Adjustment | +/- 10 degrees |
| Fine Elevation Adjustment | +/- 25 degrees |
| Mounting Pipe Diameter, Min | 4.5 inch 11.4 cm |
| Mounting Pipe Diameter, Max | 4.5 inch 11.4 cm |
| Net Weight | 85 lbs 38.3 kg |
| Wind Velocity Operational | 90 mph 145 km/h |
| Wind Velocity Survival Rating | 125 mph 201 km/h |

| | |
|--|----------------------|
| Mechanical Configuration | HP4-LoFreq |
| Axial Force (FA) | 737 lbs 3278 N |
| Side Force (FS) | 365 lbs 1623 N |
| Twisting Moment (MT) | 784 ft-lbs 1063 Nm |
| Operating Temperature Range | -40 to +60 C |
| Max Pressure, PSIG, (if waveguide interface) | na |

Regulatory Compliance

| | |
|----------------------------|------------|
| FCC | undeclared |
| Industry Canada Compliance | undeclared |

| | |
|----------------|------------|
| ETSI | undeclared |
| RoHS-compliant | Yes |

Shipping Information

| | |
|--------------|-------------------|
| Package Type | Wood Crate |
| Gross Weight | 196 lbs 88.9 kg |

| | |
|-----------------------|------------------------------------|
| Dimensions, L x W x H | 59 x 35 x 60in 180 x 89 x 152 cm |
| Shipping Volume | 71.7 cu ft 2.03 cu m |

*Additional OEM interfaces and adapters may be available. Contact RadioWaves for a complete and current list of available adapters.

TECHNICAL DRAWINGS

