



860-960 MHZ VERTICALLY POLARIZED OMNI-DIRECTIONAL ANTENNA

The NLOS series omni-directional antenna system offered by Laird Technologies are constructed of UV stabilized fiberglass and stainless steel for long service life. Mounting is easy with a dual u-bolt mounting system. The antennas are vertically polarized. The 6dBi and 8dBi come standard with 18" pigtailed terminated in an N female connector. The 5dBi and 11dBi comes standard with an integrated N Female connector. The omni's are DC grounded for lightning protection. The 11dBi omni is available with 1 deg electrical downtilt which provides null fill and improved close-in coverage.

FEATURES

- 900MHz omni-directional antenna
- Available in 5, 6, 8 and 11dBi gain models
- 1 degree electrical downtilt available on the 11dBi model
- UV stabilized fiberglass / stainless steel construction
- 18" pigtail with type N female connector standard (6dBi and 8dBi models only)


MARKETS

- 900 MHz ISM band applications
- WISP base station equipment
- Non line-of-sight applications
- Cellular applications


PARAMETER	OD9-5	OD9-6	OD9-8	OD9-11	OD9-11D1
VSWR	1.5:1	1.5:1	1.5:1	1.5:1	1.5:1
Impedance	50 ohm	50 ohm	50 ohm	50 ohm	50 ohm
Input power	100W	100W	100W	100W	100W
Pole diameter (OD)	1" - 2" (25-51mm)	1" - 2" (25-51mm)	1" - 2" (25-51mm)	1" - 2" (25-51mm)	1" - 2" (25-51mm)
Operating temperature	-45 - +70°C	-45 - +70°C	-45 - +70°C	-45 - +70°C	-45 - +70°C
Rated wind velocity	125 mph (56 m/sec)	125 mph (56 m/sec)	125 mph (56 m/sec)	125 mph (56 m/sec)	125 mph (56 m/sec)
Gain	5dBi	6dBi	8dBi	11dBi	11dBi
VSWR 1.5:1 bandwidth	890-950 MHz	865-945 MHz	865-945 MHz	860-960 MHz	860-960 MHz
VSWR 2.0:1 bandwidth		860-960 MHz	860-960 MHz		
Vertical 3dB beamwidth	36°	16°	10°	7°	7°
Electrical downtilt	0	0	0	0	1°
Length	24 in (610 mm)	5.6 ft (1.7 m)	8.5 ft (2.6 m)	11 ft (3.4 m)	11 ft (3.4 m)
Diameter	1.5 in (38 mm)	1.5 in (38 mm)	1.5 in (38 mm)	1.5 in (38 mm)	1.5 in (38 mm)

SYSTEM ORDERING


- OD9-5 5dBi slimline NLOS series 900MHz omni antenna with N female bulkhead connector
 OD9-6 6dBi NLOS series 900MHz omni antenna with 18" pigtail / N female connector
 OD9-8 8dBi NLOS series 900MHz omni antenna with 18" pigtail / N female connector
 OD9-11D1 11dBi 1deg elec downtilt NLOS series 900MHz omni antenna with integrated N female connector




OD9-5



OD9-6



OD9-8



OD9-11D1



ANT-DS-OD9 1109

All information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2009 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks or registered trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.

global solutions: local support™

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022
IAS-AsiaSales@lairdtech.com

www.lairdtech.com