


ST Splice-On Connector


For High-Density Optical Transmissions

BENEFITS AND FEATURES

- Factory installed fiber stubs using high quality fiber provide verified performance
- Factory polished and inspected ferrule end faces ensure optimum fiber optic connectivity and easy termination
- Enhanced high tensile strength for improved field terminations
- FOCIS compliant connector interfaces
- Internal testing to verify performance and compliance with Telecordia GR-326 and EIA-568
- Ideal for use in high density medium and long-range optical transmission circuits for FTTH, LAN, CATV, data center and passive optical LAN
- Swift 25-year warranty available



Swift Fusion SOC



Other Fusion SOC's




**ST
TYPE**



FIBER IDENTIFICATION

| FIBER | FIBER STUB | CONNECTOR BODY |
|----------|------------|----------------|
| OM1 | orange | beige |
| OM2 | gray | beige |
| OM3 | aqua | aqua |
| OM4 | purple | aqua |
| SM (UPC) | yellow | blue |
| SM (APC) | yellow | green |



PERFORMANCE SPECIFICATIONS

| ITEM | SINGLE MODE | | MULTI MODE |
|----------------|-----------------------------|-------|------------|
| | UPC | APC | UPC |
| Tensile | >60 newtons | | |
| Return Loss | >50dB | >60dB | >30dB |
| Insertion Loss | average <.20dB (max <.30dB) | | |

ORDERING INFORMATION

| PART NUMBER* | DESCRIPTION |
|------------------|------------------------------------|
| ST-SM-UPC-09 | Single Mode, UPC, 900 micron |
| ST-SM-UPC-20/30 | Single Mode, UPC, 2mm and 3mm |
| ST-SM-APC-09 | Single Mode, APC, 900 micron |
| ST-SM-APC-20/30 | Single Mode, SPC, 2mm and 3mm |
| ST-OM1-UPC-09 | Multit-Mode, OM1, UPC, 900 micron |
| ST-OM1-UPC-20/30 | Multit-Mode, OM1, UPC, 2mm and 3mm |
| ST-OM2-UPC-09 | Multit-Mode, OM2, UPC, 900 micron |
| ST-OM2-UPC-20/30 | Multit-Mode, OM2, UPC, 2mm and 3mm |
| ST-OM3-UPC-09 | Multit-Mode, OM3, UPC, 900 micron |
| ST-OM3-UPC-20/30 | Multit-Mode, OM3, UPC, 2mm and 3mm |
| ST-OM4-UPC-09 | Multit-Mode, OM4, UPC, 900 micron |
| ST-OM4-UPC-20/30 | Multit-Mode, OM4, UPC, 2mm and 3mm |

* Above part numbers are Simplex Connectors. For Duplex Connectors, substitute "S" with "D" in the part number.

RELATED PRODUCTS

| SYSTEM | DESCRIPTION |
|------------|--|
| KF4A | Active V-groove Clad Alignment Splicer, includes hard case (Includes (2) HS-900um holders, (1) KF4-ILC holder, (1) KF4-SC/FC holder) |
| S5 | Core Alignment Splicer, includes hard case and fixed fiber clamps. (All holders sold separately) —Fiber and Connector Holder sold separately— |
| HS-250 | 250um Fiber Holder (pair)—KF4A and S5 |
| HS-900 | 900um Fiber Holder (pair)—KF4A and S5 |
| HS-LS-900L | Loose Tube Fiber Holder (left side only)—KF4A and S5 |
| KF4-ST | ST Connector Holder—KF4A |
| HS-ST | ST Connector Holder—S5 |
| CK-01 | Splicer Cleaning Kit |
| CK-02 | Connector Cleaning Kit |
| ST-01 | ST Crimping Tool |