

Indoor PoE Lightning Surge Protector

ESWA-3310C6(⚡⚡⚡⚡⚡)

Features:

- Surge protection for PoE & Gigabit Ethernet networks
- 10/100 and 1000 Mbps data rate
- Discharge capability of 10KA
- Protects all 4 pairs
- UL497B Recognized Gas Discharge Tubes (GDT) and the network of fast response silicon avalanche diodes (SAD's) protection
- Bi-directional clamping
- High insulation resistance
- Cast aluminum construction
- Power Rating ⚡⚡⚡⚡⚡
- RoHS compliant



Specifications:

Clamping Voltage	Line-Line: 3.6 Volts Line-Ground: 90 Volts
Nominal discharge currents : -Line/Line -Line/Ground	< 25 A @ 8/20 s 10KA @ 8/20 s
Response time Line/Line Line/Ground	< 5 ns < 100 ns
Minimum Insulation Resistance	10 GΩ
Surge Rating	1,000 Watt
Protection Modes	Line-Line, Line-Ground
Standard Connectors	RJ-45 Female * 2
Case Material	Aluminum
Case Color	Black
Ground wire	12 AWG
Operating Temperature	-40°C (-40°F) to +80°C (+176°F)
Operating Humidify	0 ~ 95% non-condensing
Outside Dimensions (W*L*H)	26*26*62 mm
Weight	60 g

EverStar Vision&Communication Ltd.

No.20, Alley 7,Lane 24, Mincyuan St., Hsinchu City 30043, Taiwan R.O.C.

TEL: 886-3-5426455 FAX:886-3-5424168

Email: davidw@everstar.tw