

Data Surge Protector SPD ALPU Outdoor Gigabit Ethernet/PoE++
 Shielded RJ45 SASD, GDT CE Compliant, EN/IEC 60950-1, UL 497B



ALPU-F140

ALPU Fit

Features

- UL 497B, EN/IEC60950-1
- Gigabit Ethernet/PoE++
- Patented Weatherized Wiring Grommet
- Configurable Weep Holes
- Shielded RJ-45
- Conformal Coated PCBA
- Dielectric Lube to Weatherize RJ-45 Connections
- Pole or Wall Mount

Applications

- Gigabit Ethernet/PoE++ Networks
- Telecommunications Base Stations
- WISP/ISP
- IT & Data Centers
- Point-to-Point Links
- Control Lines and Sense Loops
- Oil & Gas

Description

Data surge protector (also known as SPD or lightning protector) ALPU-F140 from Transtector is an outdoor style SPD that utilizes state of the art SASD/GDT technology to protect critical equipment in Gigabit Ethernet/PoE++ protocol data networks while remaining transparent to data throughput. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by absorbing high amounts of transient energy while maintaining a very low clamping voltage. Transtector Data Signal surge protectors are available in stock with same day shipping.

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|-------------------------------|---------|------------------------------|---------|-------|
| Connectors | | Shielded RJ45 | | |
| Compatible Cables | | Cat5/5e UTP/STP, Cat6/6A STP | | |
| Data Protocols | | Gigabit Ethernet/PoE++ | | |
| Data Rate | | | 1,000 | Mb/s |
| Characteristic Impedance | | | 100 | Ohms |
| Power over Ethernet Protocols | | PoE++ | | |
| Vdc Rating (Data) | | 48 | 60 | Vdc |
| PoE Power | | | 100 | W |
| PoE Current Per Pin | | | 1.5 | A |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Data Surge Protector SPD ALPU Outdoor Gigabit Ethernet/PoE++ Shielded RJ45 SASD, GDT CE Compliant, EN/IEC 60950-1, UL 497B ALPU-F140](#)

Data Surge Protector SPD ALPU Outdoor Gigabit Ethernet/PoE++
 Shielded RJ45 SASD, GDT CE Compliant, EN/IEC 60950-1, UL 497B



ALPU-F140

ALPU Fit

Surge Protection Specification

| Description | Minimum | Typical | Maximum | Units |
|-----------------------------|---------|----------------------------|---------|-------|
| Surge Protection Technology | | SASD, GDT | | |
| Protected Pins | | [1,2], [3,6], [4,5], [7,8] | | |
| Protection Modes | | L-G, L-L, S-G | | |
| 8/20µs Surge Current | | | | |
| L-G | | | 2 | kA |
| L-L | | | 0.1 | kA |
| S-G | | | 20 | kA |
| Response Time | | | 5 | ns |

Mechanical Specifications

Size

| | | |
|--------|----------|------------|
| Height | 4.5 in | [114.3 mm] |
| Width | 4 in | [101.6 mm] |
| Depth | 1.7 in | [43.18 mm] |
| Weight | 0.45 lbs | [204.12 g] |

Environmental Specifications

| | |
|-----------------------|------------------|
| Operating Temperature | -40 to +65 deg C |
| Storage Temperature | -40 to +75 deg C |

| | |
|---------------------------------|---------------|
| Environmental Protection Rating | IP65, NEMA 3R |
|---------------------------------|---------------|

Installation

| | |
|-----------------------|-----------------------------|
| Mount Type | Pole/Wall |
| Installation Hardware | Combination Drive Screw |
| Grounding | #10 - #12 AWG Ring Terminal |

Compliance Certifications

| | |
|----------------|---------------------------|
| RoHS Compliant | Yes |
| CE Compliant | Yes |
| UL Compliant | Yes |
| Certifications | UL 497B EN/IEC 60950-1 |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Data Surge Protector SPD ALPU Outdoor Gigabit Ethernet/PoE++ Shielded RJ45 SASD, GDT CE Compliant, EN/IEC 60950-1, UL 497B ALPU-F140](#)

Data Surge Protector SPD ALPU Outdoor Gigabit Ethernet/PoE++
Shielded RJ45 SASD, GDT CE Compliant, EN/IEC 60950-1, UL 497B

ALPU-F140

ALPU Fit



Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: [Data Surge Protector SPD ALPU Outdoor Gigabit Ethernet/PoE++ Shielded RJ45 SASD, GDT CE Compliant, EN/IEC 60950-1, UL 497B ALPU-F140](https://www.transtector.com/data-surge-protector-spd-alpu-outdoor-gigabit-alpu-f140-p.aspx)

URL: <https://www.transtector.com/data-surge-protector-spd-alpu-outdoor-gigabit-alpu-f140-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

Data Surge Protector SPD ALPU Outdoor Gigabit Ethernet/PoE++ Shielded RJ45 SASD, GDT CE Compliant, EN/IEC 60950-1, UL 497B

ALPU-F140 CAD Drawing

| REVISIONS | | | |
|-----------|-----------------|---------|----------|
| REV. | DESCRIPTION | DATE | APPROVED |
| A | INITIAL RELEASE | 1/17/19 | DWR |

| | |
|--|---|
| <p>UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS</p> <p>TOLERANCES:</p> <p>X±.2 [5.08] FRACTIONS ±.1/32</p> <p>XX±.01 [25] ANGLES ±1°</p> <p>XXX±.005 [13]</p> <p>ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.</p> <p>THIRD-ANGLE PROJECTION</p> | <p style="text-align: center;">TRANSTECTOR</p> <p style="text-align: center;">10701 AIRPORT ROAD, HAYDEN, ID. 83835 PHONE: 1.208.635.6400 1.800.882.9110 FAX: 1.208.955.2041 www.transtector.com e-mail: sales@transtector.com</p> <p>THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF TRANSTECTOR CORPORATION. ALL RIGHTS RESERVED.</p> <p>SHEET 1 OF 1 SCALE 1:2</p> |
| <p>SIZE [CAGE] DRAWN BY PART NUMBER</p> <p>A 30992 HMB ALPU-F140</p> | <p>REV</p> <p>A</p> |

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.