



2.4 GHz, 8 dBi, Omni Antenna with N-Female Connector

Antennas Technical Data Sheet

KP-24-SPOMA-9-NF

Features

- Can be Installed in Up or Down Positions & Includes Mast Mounting Kit
- Compact, Lightweight Design Vented end Cap and Drain Holes in Base
- Economical, Compact, Lightweight Design
- Durable UV-Stable Fiberglass Radome
- Integral N-Female Connector

Applications

- 2.4 GHz ISM Band
- Supports IEEE 802.11b/g/n Applications
- WiFi and 2.4 GHz Wireless Video Systems
- Bluetooth® & Public Wireless Hotspot

Description

The KP-24-SPOMA-9-NF from KP Performance Antenna is an economical yet high performance omnidirectional Wi-Fi antenna designed for the 2.4GHz ISM band. These compact and lightweight antennas are ideally suited for IEEE 802.11b, 802.11g, 802.11n, 802.11ax (WiFi 6) wireless LANs, Bluetooth, IoT, public wireless hotspot application and other multipoint applications where wide coverage is desired.

The KP-24-SPOMA-9-NF omnidirectional antenna features an integral N-Female bulkhead type connector that mounts through the wall of an equipment enclosure. Included with the KP-24-SPOMA-9-NF is a mast mounting kit consisting of a heavy-duty steel bracket and a pair of U-bolts, this kit allows installation on masts up to 2.0" in diameter.

Constructed for all weather operation, the N-female KP-24-SPOMA-9-NF antenna features sealed collinear brass elements inside a durable UV-stable machine gray fiberglass radome. A vented end cap and drain holes in the base help prevent moisture build-up inside the antenna. These features allow the KP Performance Antenna KP-24-SPOMA-9-NF to be mounted in up or down positions. In addition to shipping the same day, our omnidirectional antennas are high-quality components backed by expert technical support and sales personnel.

Configuration

Design	Omni
Frequency Range	2.4 to 2.5 GHz
Polarization	Vertical
Connector Type	N Female
Number of Ports	1

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Impedance		50		Ohms
Gain Nominal		8		dBi
Horizontal (Azimuth) Beam Width		360		Degrees
Vertical (Elevation) Beam Width		15		Degrees
Input Power			100	Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4 GHz, 8 dBi, Omni Antenna with N-Female Connector KP-24-SPOMA-9-NF](#)



2.4 GHz, 8 dBi, Omni Antenna with N-Female Connector

Antennas Technical Data Sheet

KP-24-SPOMA-9-NF

VSWR

1.5:1

Mechanical Specifications

Radome Material

Fiberglass

Size

Base Diameter

1.27 in [32.26 mm]

Radome Diameter

0.75 in [19.05 mm]

Length

19.7 in [500.38 mm]

Weight

1.1 lbs [498.95 g]

Mounting

Mount Type

Mast

Mounting Mast Diameter

2 in [50.80 mm]

Mechanical Specification Notes:

Environmental Specifications

Temperature

Operating Range

-40 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Dedicated to serving the needs of the Wireless Internet Service Provider (WISP) market, KP Performance Antennas offers purpose built products that reliably perform in the field. KP Performance Antennas product line consists of Yagi, Grid, Omni, Dish and other style antennas that operate in the 900 MHz, 2.4 GHz, 3 GHz, and 5 GHz frequencies.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4 GHz, 8 dBi, Omni Antenna with N-Female Connector KP-24-SPOMA-9-NF](#)

URL: <https://www.kpperformance.com/2-4ghz-8dbi-omni-antenna-n-female-connector-kp-24-spoma-9-nf-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. KP Performance reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. KP Performance does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and KP Performance does not assume any liability arising out of the use of any part or documentation.

KP-24-SPOMA-9-NF CAD Drawing
2.4 GHz, 8 dBi, Omni Antenna with N-Female Connector

