



2.4 GHz and 4.9 GHz to 5.8 GHz, 3 dBi, Dual Band Omni Antenna with N-Female Connector

Antennas Technical Data Sheet

KP-25-SPOMA-3-NF

Features

- High Performance in a compact lightweight design
- Durable UV-Stable fiberglass radome with vented end cap and drain holes in base
- All weather operation
- Integral N-Female connector
- Includes mast mounting kit

Applications

- 2.4/4.9/5.1/5.3/5.4/5.8 GHz Wireless LAN systems
- IEEE 802.11a/b/g/n and 802.11ac compatible
- Homeland Security and Public Safety band
- WiMAX and WiFi applications
- Multipoint and mobile applications

Description

KP Performance Antenna's KP-25-SPOMA-3-NF with N-female connector is an economic yet high performance dual band omnidirectional antenna designed for operation in the 2.4 GHz and 4.9/5.8 GHz frequency bands. Compact and lightweight, it is ideally suited for IEEE 802.11a, 802.11b, 802.11h, 802.11j, 802.11n, 802.11ac, and 802.11ax (WiFi 6) wireless LANs and multipoint and mobile applications where high gain and wide coverage is desired.

The KP-25-SPOMA-3-NF omnidirectional antenna features an integral N-Female bulkhead type connector that can mount through the wall of an equipment enclosure. Also included is a mast mounting kit which consists of a heavy-duty steel bracket and a pair of U-bolts. This kit allows for installations on masts up to 2.0" in diameter.

A vented end cap and drain holes in the base help prevent moisture build-up inside the KP-25-SPOMA-3-NF. These features allow the antenna to be mounted in up or down positions. In addition to shipping the same day, our omnidirectional antennas are high-quality components backed by expert technical support and sales personnel.

Configuration

Design	Omni
Frequency Range	2.4 to 5.85 GHz
Gain	3.5 to 4 dBi
Polarization	Vertical
Connector Type	N Female
Number of Ports	1
Lightning Protection	DC Short

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Impedance		50		Ohms
Horizontal (Azimuth) Beam Width		360		Degrees
Vertical (Elevation) Beam Width		55		Degrees
Input Power			50	Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4 GHz and 4.9 GHz to 5.8 GHz, 3 dBi, Dual Band Omni Antenna with N-Female Connector KP-25-SPOMA-3-NF](#)



2.4 GHz and 4.9 GHz to 5.8 GHz, 3 dBi, Dual Band
Omni Antenna with N-Female Connector

Antennas Technical Data Sheet

KP-25-SPOMA-3-NF

VSWR

2:1

Specifications by Band

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	2,400-2,500	4,900-5,850				MHz
Gain	3.5	4				dBi
Maximum Input Power	50	50				Watts

Mechanical Specifications

Radome Material

Fiberglass

Size

Base Diameter

1.27 in [32.26 mm]

Radome Diameter

0.75 in [19.05 mm]

Length

4.7 in [119.38 mm]

Weight

1.2 lbs [544.31 g]

Mounting

Mount Type

Mast

Mounting Mast Diameter

1.2 to 2 in [30.48 to 50.80 mm]

Mechanical Specification Notes:

Environmental Specifications

Temperature

Operating Range

-40 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4 GHz and 4.9 GHz to 5.8 GHz, 3 dBi, Dual Band Omni Antenna with N-Female Connector KP-25-SPOMA-3-NF](#)



2.4 GHz and 4.9 GHz to 5.8 GHz, 3 dBi, Dual Band Omni Antenna with N-Female Connector

Antennas Technical Data Sheet

KP-25-SPOMA-3-NF

Dedicated to serving the needs of the Wireless Internet Service Provider (WISP) market, KP Performance Antennas offers purpose built products that reliably perform in the field. KP Performance Antennas product line consists of Yagi, Grid, Omni, Dish and other style antennas that operate in the 900 MHz, 2.4 GHz, 3 GHz, and 5 GHz frequencies.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4 GHz and 4.9 GHz to 5.8 GHz, 3 dBi, Dual Band Omni Antenna with N-Female Connector KP-25-SPOMA-3-NF](https://www.kpperformance.com/2-4ghz-and-4-9ghz-to5-8ghz-3dbi-dual-band-omni-antenna-n-female-connector-kp-25-spoma-3-nf)


URL: <https://www.kpperformance.com/2-4ghz-and-4-9ghz-to5-8ghz-3dbi-dual-band-omni-antenna-n-female-connector-kp-25-spoma-3-nf-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. KP Performance reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. KP Performance does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and KP Performance does not assume any liability arising out of the use of any part or documentation.

KP-25-SPOMA-3-NF CAD Drawing

2.4 GHz and 4.9 GHz to 5.8 GHz, 3 dBi, Dual Band Omni Antenna with N-Female Connector

REVISIONS		
REV.	DESCRIPTION	DATE
A	INITIAL RELEASE	09/02/2020
		APPROVED KHETPAS



 <small>THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF KP PERFORMANCE, INC. ALL RIGHTS RESERVED.</small>		SHEET 1 OF 1
 an INFINIT brand 15397-117 Ave. Edmonton, Alberta, Canada T5M3X4 Phone: 1.855-276-5772 Edm.: 1.780.702.7577 www.kpperformance.com Email: info@kpperformance.com		SCALE N/A
<small>UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS</small>	<small>TOLERANCES:</small> X = ±.2 [5.08] FRACTIONS XX = ±.02 [51] +.132 XXX = ±.005 [13] ANGLES ± 1°	ITEM NO. REV A N/A DZINN KP-25-SPOMA-3-NF A
<small>CABLE LENGTH (L) TOLERANCES: L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5% / -0</small>		<small>ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.</small>

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

T1Rev D