



# Cleavers

## Auto Rotation Blade Cleavers

- Single Action(Full Automatic) for changing channel, cleaving & collecting fiber chips
- Blade Life time 75,000fibers (No setup is required when replacing blade)
- Oil Damper System

**CS-01AT**



**CI-03RT**



**CI-03BT**



**CS-01BT**



CATEGORY		CS-01AT	CS-01BT	CI-03BT	CI-03RT
Bare Fiber Diameter		125μm	125μm	125μm	125μm
Coating Diameter		250 ~ 900μm, IN-DOOR	250 ~ 900μm, IN-DOOR	250 ~ 900μm	250 ~ 900μm
Cleave Angle		0.5°	0.5°	0.5°	0.7°
Blade Lifetime*		75,000 fibers	75,000 fibers	75,000 fibers	75,000 fibers
Applicable Splicer		K11, K9, KF4	K11, K9, KF4	K11, K9	KR7
Cleave Lengths	Universal Holder	Single 7mm ~ 16mm	Single 7mm ~ 16mm	Single 10mm ~ 16mm	X
	Exchange Holder	Single 7.5mm(SOC)	Single 7.5mm(SOC)	Single 10mm	Ribbon 10mm
Dimensions		58×58×50mm	90×58×50mm	90×58×50mm	90×58×50mm
Weight		244g	276g	276g	260g
Chip-Box		X	O	O	O

\* Blade lifetime is not guaranteed. It may vary depending on the operating environment.

• Specifications are subject to change without prior notice.





# Cleavers

## Fiber Cleavers


- Economical Price
- Compact Design

### CI-03

**CI-03A**  
(Without ChipBox)



**CI-03B**  
(With ChipBox)



CATEGORY	CI-03A	CI-03B
Bare Fiber Diameter	125μm	
Coating Diameter	250 ~ 900μm	
Cleave Angle	0.5°	
Blade Lifetime*	50,000 fibers	
Cleave Length	Single 10mm ~ 16mm	
Dimensions	58×58×50mm	90×58×50mm
Weight	244g	276g
Chip-Box	X	O

### CI-01



Bare Fiber Diameter	125μm
Coating Diameter	250 ~ 900μm
Cleave Angle	0.5°
Blade Lifetime*	50,000 fibers
Applicable Splicer	K9, K11
Cleave Length	Single 10mm ~ 16mm
Dimensions	58×58×50mm
Weight	244g

### CI-06



Cleave Angle	0.5°
Cleave Life	2,000
Dimension	19×32×124mm
Weight	70g

### CI-08

- Typical Cleaving Angle Deviation: 6° ~ 9°
- Just one touch for tension, twisting, cleaving
- Oil Damper System



Bare Fiber Diameter	125μm
Coating Diameter	250 ~ 900μm
Cleave Angle	06° ~ 9°
Blade Lifetime*	Max. 30,000 fibers
Dimensions	104×72×56mm
Weight	400g

### CS-03A



Bare Fiber Diameter		125μm
Coating Diameter		250 ~ 900μm, IN-DOOR
Cleave Angle		0.5°
Blade Lifetime*		50,000 fibers
Applicable Splicer		KF4,K11
Cleave Lengths	Universal Holder	Single 10mm ~ 16mm
	Exchange Holder	Single 7.5mm (SOC)
Dimensions		58×58×50mm
Weight		244g

\* Blade lifetime is not guaranteed. It may vary depending on the operating environment.  
 \* Specifications are subject to change without prior notice.

#### UCLSWIFT KOREA

#39, Techno 3-ro, Yuseong-gu, Daejeon, Korea (Zip. 305-509) | Tel +82 42.671.5610 | Fax +82 42.671.5612 | sales@uclswift.com

**USA** 4230 LBJ Freeway, Ste.149 Dallas, TX 75244 | (+1) 972 556 0916

**INDIA** ILSintech Trading India Pvt.Ltd 621, Devika Tower, Nehru Place New Delhi 110019 | (+91) 11 4055 5954

**CHINA** Room 101 Li Ming Building, No111 Gui Qing Road Xuhui District, Shanghai, China | (+86) 21 5836 0950

**RUSSIA** Office 401(Kotra) 4F Hotel "Korston" 15 st. Kosygina, Moscow, Russia | (+7) 985 9111987

**EUROPE** Zirovnicka 2/2389 106 00 Prague 10, Prague, Czech Republic | (+420) 725 001 757

**INDONESIA FACTORY** Dusun 02 Blok Babakan RT01/Rw03, Desa Sukaraja Wetan, Jatiwangi, Majalengka, Jawa Barat, Indonesia

