



## SRA09/24/50

### Key Features:

- Tri-Band 900MHz, 2.4GHz & 5GHz Directional Gain
- Three Antennas in One Case
- Integrated enclosure
- Mounting for Mikrotik 411, 433, 600, series
- Mounting for Ubiquiti Rocket
- High Quality Construction
- Heavy-Duty Mounting Elements
- Easy Elevation and Tilt Adjustment
- 5 Years Warranty
- Designed for All Weather Operation



### Applications:

- 900MHz, 2.4GHz, 5 GHz Band Wireless LAN
- WLAN Systems
- Point to Point Applications

### Available in E version

SRA09/24/50-e

Economy version with cable gland.

### Description:

Antenna with multipurpose enclosure working in tri-band 900MHz, 2.4GHz & 5GHz with three independent directional panel antennas with 10dBi, 14dBi & 19dBi gain respectively. Antenna works with vertical and horizontal polarization. The range includes weatherproof outdoor enclosure with panel antenna and enough compartment for RouterBoard or any other electronic equipment. Enclosure is furnished with special RJ-45 waterproof ethernet connector with an easy connection to Internet Network and PoE. Perfectly designed for

operation under severe weather conditions. Proper materials allow operation in the salty water environment without corrosion. High quality construction of pole mounting elements guarantee easy elevation and easy tilt down as well as rock-stable operation. It can be used as customer premise equipment and also as a base stations. Inside the enclosure there are suitable posts for all Mikrotik Routerboards, mounting for Ubiquiti Rocket and for other radios.

<b>Electrical Properties</b>	
Frequency	900MHz, 2.4GHz & 5GHz
Gain	10dBi, 14dBi & 19dBi
Polarization	horizontal or vertical
Beamwidth deg horizontal	55°, 38°, 20 °
Beamwidth deg vertical	60°, 38°, 20 °
VSWR	<2
Impedance	50 ohm
Front to back ratio	> 20 dB
Port Isolation	> 40 dB
<b>Enclosure Properties</b>	
Technology:	Microstrip
Material:	UV protected
Colour:	Grey
Min temperature:	-40°C / -40°F
Max temperature:	80°C / 176°F
<b>Mechanical Properties</b>	
Compatible with:	RB411, RB433 and RB600 series
Input Connector	3x pigtail UFL, MMCX or RPSMA
Enclosure Connector	Waterproof Ethernet Connector RJ45 (or cable gland optional)
Outside Dimensions	385x385x80mm /
Weight	2.4kg / 5.3lbs

Specification subject to change without notice.