

## **TPSK Series**

# **DATA SHEET**

## **Solar Kits**

#### **Features**

- Complete Kit Solar Panel, Pole/Wall Mount, Outdoor 12AWG Cable, Battery Charge Controller
- Accommodates 2" to 4.5" dia. Pole or Wall Mount
- Quick tilt adjustment (15° to 65°)
- Certified for up to 110MPH Winds

## **Applications**

- Remote Power Stations
- Lighting Applications
- Wireless Base Stations
- Surveillance Applications



160W and 320W Kit Mount System

#### **Description**

The TPSK series of solar panel kits come complete with high efficiency multicrystalline solar panel, side of pole/wall mounts, PWM Charge Controller and outdoor rated 12AWG cable. They are ready for quick connection to Tycon Power® outdoor UPSPro™ Systems or any other application requiring solar power. The panels provide excellent low light performance and long life (25years). The rugged aluminum frame and high transparency, low iron, tempered glass withstands high wind, hail and snow loading. The mounts are heavy duty aluminum with stainless steel hardware. They are a simplified design that makes them easy to install, saving precious installer time. The mounts are designed for pole mounting but can also be wall mounted. They provide quick tilt adjustment for positioning the panel to proper sun angles for summer and winter sun.

#### **Specifications**

	TPSK12-30W	TPSK24-30W	TPSK12-80W	TPSK12/24- 160W	TPSK12/24- 320W
Solar Panel Voltage/Capacity	12V 30W	24V 30W	12V 80W	12V/24V 160W	12V/24V 320W
Solar Panel Max Current	1.74A	0.87A	4.43A	8.86A	17.72A
Solar Panel Size	16" x 26"	20" x 21"	26" x 34"	26" x 68"	52" x 68"
Solar Panel Model	TPS-12-30W	TPS-24-30	TPS-12-80W	TPS-12-80W x 2	TPS-12-80W x 4
Pole Diameter	2" to 4.5"	2" to 4.5"	2" to 4.5"	2" to 4.5"	2" to 4.5"
Pole Mount Model	TPSM-30-80-SP	TPSM-30-80-SP	TPSM-30-80-SP	TPSM-80x4-UNI	TPSM-80x4-UNI
Wind Speed Rating	110MPH	110MPH	110MPH	90MPH	90MPH
Charge Controller Model	TP-SC24-20	TP-SC24-20	TP-SC24-20	TP-SC24-20	TP-SC24-20
Cable – 2 Cond – Outdoor	12AWG x 10'	12AWG x 10'	12AWG x 10'	12AWG x 20'	12AWG x 20'
Operating Temperature	-40C to +85C	-40C to +85C	-40C to +85C	-40C to +85C	-40C to +85C
Shipping Weight	8.2kg (18lb)	8.2kg (18lb)	10kg (22lb)	24kg (53lb)	36kg (79lb)

Solar Kits	olar Kits Description		Continuous Power with 3 Hours Peak Sun	
TPSK12-30W	12V 30W Solar Kit	8W	4W	
TPSK24-30W	24V 30W Solar Kit	8W	4W	
TPSK12-80W	12V 80W Solar Kit	20W	10W	
TPSK12/24-160W	12V/24V 160W Solar Kit	40W	20W	
TPSK12/24-320W	12V/24V 320W Solar Kit	80W	40W	





12V / 24V Intelligent Solar Charge Controller



20' Outdoor Rated 12AWG Cable

#### For further information contact:

Tyconsystems.com





14641 S 800 W Bluffdale, UT 84065 PH: 801-432-0003 FAX: 801-618-4220