

Specifications Sheet



Motorola Canopy 5.4 GHz SM



Canopy Part Number	5400SM
Description	5.4 GHz SM
Market Availability	not currently available in the US
Signaling Rate	10 Mbps, 20 Mbps with Advantage AP
Typical LOS Range	3.2 km (2 Miles)
Typical Aggregate Useful Throughput	7 Mbps
Frequency range of band	U-NII 5470-5725 MHz
Channel Width	20 MHz
Modulation Type	High Index 2-level and 4-level Frequency Shift Keying (FSK) optimized for interference rejection
Channel Spacing	configurable on 5 MHz increments
Encryption	DES capable
Latency	6 msec with Advantage AP, 15 msec with Canopy AP
Carrier to Interference ratio (C/I)	-3dB @ 10 Mbps, -10dB @ 20 Mbps at -65dBm
Nominal Receiver Sensitivity (dbm typical)	-86 dBm
Antenna Gain (dB)	7 dBi
EIRP (dB)	30 dBm
Equivalent Isotropic Radiated Power (EIRP)	Adjustable to 1 W
DC Power (typical)	0.3A @ 24VDC = 7.2 W
Antenna Beam Width	3 dB antenna beam width 60 degrees, azimuth and elevation
Mean Time Between Failure (MTBF)	40 years
Temperature	-40° C to +55° C (-40° F to +131° F)
Wind Survival	190 km/hr (118 miles/hr)
Dimensions	11.75 in H x 3.4 in W x 3.4 in D (29.9 cm H x 8.6 cm W x 8.6 cm D)
Weight	.45 kg (1 lb)
Access Method	Time Division Duplexing/Time Division Multiple Access (TDD/TDMA)
Interface	10/100 Base T, half/full duplex. Rate auto negotiated (802.3 compliant)
Protocols Used	IPv4, UDP, TCP, ICMP, Telnet, HTTP, FTP, SNMP
Network Management	HTTP, TELNET, FTP, SNMP Version 2c
CE	"CE" marked & compliant to EN301 893, Implements DFS & TPC. DoCs are available at http://www.canopywireless.com/doc.php

Specifications subject to change without notice.

MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. All other product or service names are the property of their respective owners. © Motorola, Inc. 2007