

Smart-UPS SC

APC Smart-UPS SC 420VA 120V

APC Smart-UPS SC, 260 Watts / 420 VA, Input 120V / Output 120V, Interface Port DB-9 RS-232



Includes: CD with software, Smart UPS signalling RS-232 cable, User Manual

Standard Lead Time: Usually in Stock

Smart-UPS SC Features & Benefits

Manageability

- Network manageable Provides remote management of the UPS over the network.
- Audible Alarms Actively let you know if the unit is on battery, if the battery is low or if there is an overload condition.
- Automatic self-test Periodic battery self-test ensures early detection of a battery that needs to be replaced.
- Battery failure notification Provides early-warning fault analysis on batteries enabling timely preventive maintenance
- Serial Connectivity Provides management of the UPS via a serial port.
- LED status indicators Quickly understand unit and power status with visual indicators.
- InfraStruXure Manager Compatible Enables centralized management via the APC InfraStruXure® Manager.

Economy

- Boost and Trim Automatic Voltage Regulation (AVR) Gives higher application availability by correcting low and high voltage conditions without using the battery.
- Adjustable voltage-transfer points Maximizes useful battery life by widening the input voltage window or tightening the output voltage regulation.
- Safety-agency approved Ensures the product has been tested and approved to work safely with the connected service provider equipment and within the specified environment. UL, FCC, CE, C-Tick approvals.

Availability

- Dataline Surge Protection Provides protection of connected equipment from power surges on the data lines.
- Power conditioning Protects connected loads from surges, spikes, lightning, and other power disturbances.
- Intelligent Battery Management Maximizes battery performance, life, and reliability through intelligent, precision charging.
- Automatic restart of loads after UPS shutdown Automatically starts up the connected equipment upon the return of utility power.
- Cold-start capable Provides temporary battery power when the utility power is out.
- Hot-swappable batteries Ensures clean, uninterrupted power to protected equipment while batteries are being replaced
- Resettable circuit breakers Enables a quick recovery from overload events.

Output

Output Power Capacity	260 Watts / 420 VA
Max Configurable Power	260 Watts / 420 VA
Nominal Output Voltage	120V
Output Voltage Distortion	Less than 5% at full load
Output Frequency (sync to mains)	47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal
Crest Factor	up to 5 : 1
Waveform Type	Stepped approximation to a sinewave
Output Connections	(4) NEMA 5-15R



Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	NEMA 5-15P
Cord Length	1.83 meters
Input voltage range for main operations	82 - 144V
Input voltage adjustable range for mains operation	75 - 154V



Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	5 hour(s)
Replacement Battery	RBC2 , RBC2J
RBC™ Quantity	1
Typical Backup Time at Half Load	13.5 minutes (130 Watts)
Typical Backup Time at Full Load	5.5 minutes (260 Watts)
Runtime Chart	Smart-UPS SC

Communications & Management

Interface Port(s)	DB-9 RS-232
-------------------	-------------

Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off (EPO)	Optional

Surge Protection and Filtering

Surge energy rating	412 Joules
Filtering	Full time multi-pole noise filtering : 0.7% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	RJ-45 Modem/Fax/DSL/10-100 Base-T protection

Physical

Maximum Height	168.00 mm
Maximum Width	119.00 mm
Maximum Depth	368.00 mm
Net Weight	10.00 KG
Shipping Weight	10.91 KG
Shipping Height	318.00 mm
Shipping Width	262.00 mm
Shipping Depth	508.00 mm
Color	Grey
Units per Pallet	40.00

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0%
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.00 dBA
Online Thermal Dissipation	50.00 BTU/hr

Conformance

Regulatory Approvals

CSA,FCC Part 15 Class A,UL 1778

Standard Warranty

2 years repair or replace

**The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the UPS.